



Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-2818-2	Version number:	22.01
Revision date:	22/07/2022	Supersedes date:	19/11/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ TroubleShooter™ Baseboard Stripper

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Baseboard Stripper

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for eye damage/irritation and the test results are reflected in the assigned classification.

This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

CLASSIFICATION:

Aerosol, Category 3 - Aerosol 3; H229

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |

Pictograms



HAZARD STATEMENTS:

H229	Pressurised container: may burst if heated.
H314a	Causes severe skin burns.
H319	Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P260E	Do not breathe vapour or spray.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH071	Corrosive to the respiratory tract.
--------	-------------------------------------

9% of the mixture consists of components of unknown acute oral toxicity.
9% of the mixture consists of components of unknown acute dermal toxicity.
9% of the mixture consists of components of unknown acute inhalation toxicity.

Notes on labelling

Updated per Regulation (EC) No. 648/2004 on detergents. Nota K applied.
Ingredients required per 648/2004 (not required on industrial label): <5%: Non-ionic surfactants. Contains: Perfumes, d-limonene.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	Mixture	60 - 90	Substance not classified as hazardous
2-butoxyethanol	(CAS-No.) 111-76-2 (EC-No.) 203-905-0	10 - 15	Acute Tox. 4, H332 Acute Tox. 4, H302(LD50 = 1200 mg/kg **ATE values per Annex VI**) Skin Irrit. 2, H315 Eye Irrit. 2, H319
Petroleum gases, liquefied, sweetened	(CAS-No.) 68476-86-8 (EC-No.) 270-705-8	5 - 10	Liquefied gas, H280 Nota K,S,U STOT SE 3, H336
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3	< 4 - 5	Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Chronic 3, H412
Alcohols, C12-15, ethoxylated	(CAS-No.) 68131-39-5 (EC-No.) 500-195-7	< 0.9 - 1	Aquatic Acute 1, H400,M=1 Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3	(C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. Get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralise spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralising agent until reaction stops. Let cool before collecting. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material

as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-butoxyethanol	111-76-2	UK HSC	TWA:123 mg/m ³ (25 ppm);STEL:246 mg/m ³ (50 ppm)	SKIN
2-aminoethanol	141-43-5	UK HSC	TWA:2.5 mg/m ³ (1 ppm);STEL:7.6 mg/m ³ (3 ppm)	SKIN

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
2-butoxyethanol	111-76-2	UK EH40 BMGVs	Butoxyacetic acid	Creatinine in urine	EOS	240 mmol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Fluoroelastomer	0.4	=>8 hours
Polymer laminate	>0.30	4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

Half facepiece or full facepiece supplied-air respirator

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter type A

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state

Liquid.

Specific Physical Form:

Aerosol

Colour

Off-White

Odor

Petroleum

Odour threshold

No data available.

Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	> 100 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	No flash point
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	11 - 12.1
Kinematic Viscosity	80.2 mm ² /sec
Water solubility	Complete
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	0.967 g/ml - 1.027 g/ml
Relative density	0.967 - 1.027 [Ref Std:WATER=1]
Relative Vapor Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Percent volatile	60 - 90 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient

classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-butoxyethanol	Inhalation-Vapour (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-butoxyethanol	Ingestion	Guinea pig	LD50 1,200 mg/kg
Petroleum gases, liquefied, sweetened	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
2-aminoethanol	Inhalation-Vapour	official classification	LC50 estimated to be 10 - 20 mg/l

2-aminoethanol	Dermal	Rabbit	LD50 2,504 mg/kg
2-aminoethanol	Ingestion	Rat	LD50 1,089 mg/kg
Alcohols, C12-15, ethoxylated	Dermal	Rat	LD50 5,000 mg/kg
Alcohols, C12-15, ethoxylated	Ingestion	Rat	LD50 1,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
2-butoxyethanol	Rabbit	Irritant
Petroleum gases, liquefied, sweetened	Professional judgement	No significant irritation
2-aminoethanol	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Professional judgement	Severe irritant
2-butoxyethanol	Rabbit	Severe irritant
Petroleum gases, liquefied, sweetened	Professional judgement	No significant irritation
2-aminoethanol	Rabbit	Corrosive
Alcohols, C12-15, ethoxylated	Not available	Corrosive

Skin Sensitisation

Name	Species	Value
2-butoxyethanol	Guinea pig	Not classified
2-aminoethanol	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Petroleum gases, liquefied, sweetened	In Vitro	Not mutagenic
2-aminoethanol	In Vitro	Not mutagenic
2-aminoethanol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2-butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
2-aminoethanol	Dermal	Not classified for development	Rat	NOAEL 225 mg/kg/day	during organogenesis
2-aminoethanol	Ingestion	Not classified for development	Rat	NOAEL 616 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Petroleum gases, liquefied, sweetened	Inhalation	cardiac sensitisation	Causes damage to organs	similar compounds	NOAEL Not available	
Petroleum gases, liquefied, sweetened	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Petroleum gases, liquefied, sweetened	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
2-aminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available

3M™ Troubleshooter™ Baseboard Stripper

2-butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
Petroleum gases, liquefied, sweetened	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
2-aminoethanol	Inhalation	liver kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 0.656 mg/l	5 weeks
2-aminoethanol	Ingestion	hematopoietic system liver kidney and/or bladder respiratory system	Not classified	Rat	NOAEL Not available	

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2-butoxyethanol	111-76-2	Activated sludge	Experimental	16 hours	IC50	>1,000 mg/l
2-butoxyethanol	111-76-2	Eastern oyster	Experimental	96 hours	LC50	89.4 mg/l
2-butoxyethanol	111-76-2	Green algae	Experimental	72 hours	ErC50	1,840 mg/l
2-butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l
2-butoxyethanol	111-76-2	Green algae	Experimental	72 hours	ErC10	679 mg/l
2-butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l

Petroleum gases, liquefied, sweetened	68476-86-8		Data not available or insufficient for classification			n/a
2-aminoethanol	141-43-5	Activated sludge	Experimental	30 minutes	EC10	>1,000 mg/l
2-aminoethanol	141-43-5	Common Carp	Experimental	96 hours	LC50	349 mg/l
2-aminoethanol	141-43-5	Green algae	Experimental	72 hours	EC50	2.5 mg/l
2-aminoethanol	141-43-5	Water flea	Experimental	48 hours	EC50	65 mg/l
2-aminoethanol	141-43-5	Green algae	Experimental	72 hours	NOEC	1 mg/l
2-aminoethanol	141-43-5	Medaka	Experimental	41 days	NOEC	1.24 mg/l
2-aminoethanol	141-43-5	Water flea	Experimental	21 days	NOEC	0.85 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Bacteria	Estimated	16.9 hours	EC10	>10,000 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Diatom	Experimental	72 hours	EC50	1 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Fathead minnow	Experimental	96 hours	LC50	0.48 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Green algae	Experimental	72 hours	EC50	0.85 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Water flea	Experimental	48 hours	EC50	0.14 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Diatom	Experimental	72 hours	NOEC	0.32 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Green algae	Experimental	72 hours	NOEC	0.5 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Water flea	Experimental	21 days	NOEC	0.083 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Experimental Biodegradation	28 days	CO2 evolution	90.4 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
2-butoxyethanol	111-76-2	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	100 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
Petroleum gases, liquefied, sweetened	68476-86-8	Data not available or insufficient	N/A	N/A	N/A	N/A
2-aminoethanol	141-43-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	>90 % weight	OECD 301A - DOC Die Away Test
Alcohols, C12-15, ethoxylated	68131-39-5	Experimental Biodegradation	28 days	CO2 evolution	64-79 % weight	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.81	
Petroleum gases, liquefied, sweetened	68476-86-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Petroleum gases, liquefied, sweetened	68476-86-8	Estimated Bioconcentration		Log Kow	2.8	
2-aminoethanol	141-43-5	Experimental Bioconcentration		Log Kow	-2.3	
Alcohols, C12-15, ethoxylated	68131-39-5	Experimental BCF - Fish	72 hours	Bioaccumulation factor	310	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Estimated Mobility in Soil	Koc	67 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 070704* Other organic solvents, washing liquids and mother liquors
- 16 05 04* Gases in pressure containers (including halons) containing dangerous substances

EU waste code (product container after use)

- 15 01 04 Metallic packaging

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS, NON-FLAMMABLE, CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP III	AEROSOLS

14.3 Transport hazard class(es)	2.2(8)	2.2(8)	2.2(8)
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	5C	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2-butoxyethanol	111-76-2	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components

of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
Petroleum gases, liquefied, sweetened	68476-86-8	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H314a	Causes severe skin burns.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Label: CLP Precautionary - Storage information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 04: First Aid - Symptoms and Effects (CLP) information was added.

Section 04: Information on toxicological effects information was modified.

Section 09: Kinematic Viscosity information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was added.

Section 11: Target Organs - Repeated Table information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was added.

Section 12: No Data text for mobility in soil information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was modified.

Section 14 UN Number information was modified.

Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk