



▶ DPF 50WD Clear

Promotional Removable Film

DPF 50WD Clear is a 100 microns clear vinyl film with a clear low tack removable pressure-sensitive adhesive. The low tack adhesive is designed to bond well to glass surfaces while removing cleanly in a wide range of temperatures. DPF 50WD Clear has a premium moisture stable polycoated lay-flat liner that is optimal for printing on a variety of print systems. DPF 50WD Clear is rated for outdoor durability up to 1 year (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Window advertising and decals
- Displays on high energy substrates such as glass, aluminum or other metals
- Horizontal POP applications (excluding floor graphics)
- Digital printing with a wide variety of direct print systems, such as solvent, UV, and UV screen
- Compatible with Series 3200
- Recommended with dry application methods only

PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE
SURFACE FINISH	Gloss Meter 60° Reflection	99%
THICKNESS	Micrometer, Federal Bench Type	100 microns
TENSILE STRENGTH	Tensile Tester 51 mm jaw separation; crosshead speed of 5.1 mm/s	3.93 kg/cm
ELONGATION	Instron Tensile Tester as above	250%
SHELF LIFE	Free from excessive moisture, temperature, direct sunlight	2 Years
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	10°C to 30°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-29°C to 80°C
DIMENSIONAL STABILITY	Shrinkage After 70°C, 48 hours aging	0.635 mm
PEEL ADHESION	PSTC-1, 15 min, RT 21°C	0.03 kg/cm
LINER RELEASE	TLMI Release at 90°, 760 cm/min	4.92 g/cm

Standard Terms & Conditions Apply

USA

200 Boysenberry Lane, Placentia, CA 92870
 800 232 7161/+1 714 985 6300
 +1 714 985 6305

EUROPE

Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
 +31 70 354 4311
 +31 70 355 7721

CHINA

No. 1989 Xinchang Road, Weifang, Shandong, 262400
 +86 0536 6226568

TERMS & CONDITIONS


The following is made in lieu of all warranties expressed or implied:


All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

April 2020

USA

 200 Boysenberry Lane, Placentia, CA 92870

 800 232 7161 / +1 714 985 6300

 +1 714 985 6305

EUROPE

 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands

 +31 70 354 4311

 +31 70 355 7721

CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400

 +86 0536 6226568