3M Commercial Graphics Colour Card Reference Guide



3M[™] Envision[™] Translucent Films IJ3730-50, IJ3730-60 3M[™] Envision[™] Diffuser Films 3735-50, 3735-60

The first graphic films that optimize LED light




Colour Card Reference



High Performance for ElectroCut illuminated



Guide



All printed examples of colours are approximations of the original colours and are subject to fluctuations due to the printing process. To determine the exact colour or choice of colours, please request an original 3M colour swatch or individual colour samples of your preferred colours.

Films and printed graphics



3M[™] Envision[™] Translucent Film Series 3730 3M[™] Envision[™] Translucent Films IJ3730-50, IJ3730-60 3M[™] Envision[™] Diffuser Films 3735-50, 3735-60

Stay bright

3M technology makes it easy and practical to use LEDs. Get the same level of brightness using fewer light sources, reducing material and maintenance costs. Get more light transmission for vibrant, rich colour.

Go greener

3M[™] Envision[™] Translucent and Diffuser Films give your customers the opportunity to be more sustainable without sacrificing performance. They'll get an energy-saving, premium product backed by an industry-leading warranty. So they won't just look good – they'll feel good, too.

You win. They win. The environment wins.

Product Data

Product Features

• Suitable for interior and exterior applications

• Typical applications

Illuminated advertising, illuminated strips, filling stations, shopwindows and restaurants. Wherever you wish to advertise, whether by day or by night. Colour fastness and dimensional stability ensure reliability, and the brilliance of the films ensures a high level of attention.

- Suitable application surfaces and substrates
 3M[™] Envision[™] Translucent Graphic Film Series 3730
 is excellently suited for application to glass and acrylic surfaces
 and will also ensure perfect presentation of your brand on
 3M[™] Flexible Substrates.
- Graphic durability

Up to 10 years*

• Colour range

20 luminous standard colours provide extensive design freedom. The option of requesting your individual special colours means that the special requirements of your corporate image can also be fulfilled.

The range is completed by Envision Diffuser Films 3735-50 and 3735-60 and version IJ3730-50 and IJ3730-60, which enable digital printing.

Application temperature range, wet-bonded

from +16°C

*See relevant technical bulletin for full details. Further information and samples on request.

• Suitable graphic production processes easyly cut, thanks to polyester protective paper

All colours with Pantone references are a simulation of a PANTONE[®]-identified colour standard.

Evaluation illuminant: D6500K a viewed in the Pantone[®] Viewing light. Consult current PANTONE Colour Publications for accurate colour. PANTONE[®] is the property of Pantone, Inc. ©Pantone, Inc., 2010



