2 - 5 μm (0.1 - 0.2 mil)



FUSION PLUS™ **SATIN**, a tailor-made ceramic coating for satin paint and XPEL **STEALTH™** paint protection film. Delivering exceptional hydrophobicity and ease of maintenance. Safeguards your vehicle's finish against oxidation, gloss loss, UV damage, and color fading, ensuring lasting protection and visual appeal.fading, ensuring lasting protection and visual appeal.

PRODUCT CONSTRUCTION

COATING THICKNESS

GENERAL CHARACTERISTICS	
PROPERTIES	INFORMATION
Pencil Hardness	9Н
Bottle Size	50ml
Shelf Life	1 Year from ship date when unopened and stored dry at 72° F (22° C) @ 50% RH. Once opened and stored properly, use within 14 days
Application	Foam Block with microsuede towel
Appearance	Clear
Temperature Resistance	>760 Degrees Celsius
Mandrel Bend	(ASTM D522) 0% at 180 Degree Rotation
Dry Time	4 Hours before getting wet
Cure Time	3 days



Notice: The representations of performance and suitability for use contained in this Technical Data Sheet are meant only as a guide. Since only the user is aware of the specific conditions in which the product is to be used, it is the user's responsibility to determine whether the product it suitable for that intended use.